




Clip-On Series

The Clip-On Gaskets are used in enclosures, shielded cabinets, and on circuit cards as ESD contacts and EMI gaskets. For edge mount applications, close attention must be given to clip size, lance requirements, deflection parameters and finger configuration. Leader Tech provides application assistance in the development of specifications.

C Clip-On		Black = inches Red= mm Comp = Compressed																									
P/N	A	B	Finger	Pitch	Mat. Thick	Comp Width	Comp Height	Lance Start	Lance Pitch	Length	Fingers	Clip ID	Lance														
10-30C-045-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	16	406	86	.045	n/a								
10-30C-050-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	16	406	86	.050	n/a								
10-30C-065-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	16	406	86	.065	n/a								
10-30C-070-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	16	406	86	.070	n/a								
10-30C-045-DL-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	0.481	12.2	1.000	25.4	16	406	86	.045	D				
10-30C-050-DL-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	0.481	12.2	1.000	25.4	16	406	86	.050	D				
10-30C-065-DL-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	0.481	12.2	1.000	25.4	16	406	86	.065	D				
10-30C-070-DL-XX-16	0.10	2.5	0.30	7.6	0.14	3.6	0.187	4.75	0.005	0.127	0.330	8.38	0.050	1.27	0.481	12.2	1.000	25.4	16	406	86	.070	D				
11-45C-045-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40					16	406	86	.045	n/a				
11-45C-050-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40					16	406	86	.050	n/a				
11-45C-065-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40					16	406	86	.065	n/a				
11-45C-070-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40					16	406	86	.070	n/a				
11-45C-045-DL-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40	0.481	12.2	1.000	25.4	16	406	86	.045	D				
11-45C-050-DL-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40	0.481	12.2	1.000	25.4	16	406	86	.050	D				
11-45C-065-DL-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40	0.481	12.2	1.000	25.4	16	406	86	.065	D				
11-45C-070-DL-XX-16	0.11	2.8	0.45	11.4	0.14	3.6	0.187	4.75	0.005	0.127	0.470	11.94	0.055	1.40	0.481	12.2	1.000	25.4	16	406	86	.070	D				
25-109C-070-XX-16	0.25	6.4	1.09	27.7	0.34	8.5	0.375	9.53	0.005	0.127	1.270	32.26	0.080	2.03					16	406	43	.070	n/a				
25-109C-070-DL-XX-16	0.25	6.4	1.09	27.7	0.34	8.5	0.375	9.53	0.005	0.127	1.270	32.26	0.080	2.03					0.700	17.78	1.125	28.58	16	406	43	.070	D
25-109C-120-XX-16	0.25	6.4	1.09	27.7	0.34	8.5	0.375	9.53	0.005	0.127	1.27	32.26	0.080	2.03									16	406	43	0.12	n/a
25-109C-130-XX-16	0.25	6.4	1.09	27.7	0.34	8.5	0.375	9.53	0.005	0.127	1.27	32.26	0.080	2.03													16



MOUNTING OPTIONS
 ■ Clip

Consult factory for optional clip sizes and optional lance features.
 XX - Select material/finish (see page 16)