

TGF15

Leader Tech's TGF15 series is a reliable heat transfer media with excellent insulation, compressibility and natural surface viscosity. It conforms perfectly with surface gaps, allowing it to fill air gaps and heat conduction from a heat source to a surface.

Features:

- Low thermal resistance
- UL94 V-0 recognized
- Excellent compression rate
- RoHS and Reach Compliant

Applications:

- Between chip and heat-dissipation modules
- Optoelectronics industry
- Netcom products
- New energy Battery and Automotive Industry
- Household Appliances
- Wearable Technology

Storage Conditions:

- Store in the darkness
- Storage Temperature: $\leq 30^{\circ}\text{C}$
- Storage Humidity: $\leq 70\%$
- When stacking the parts, the parts should not be higher than 7 layers or more than 1mm

Shelf Life:

- Stored at storage conditions: Two years
- Stored in unqualified storage conditions: 6 months

Properties:

Item	Parameter	Unit	Test Method
Color	Pink	-	Visual
Thickness	0.3 ~ 18	mm	ASTM D374
Hardness	10 ~ 75 (± 10)	Shore 00	ASTM D2240
Density	2.62(± 0.5)	g/cc	ASTM D792
Tensile Strength	≥ 0.25	Mpa	ASTM D412
Elongation	≥ 80	%	ASTM D412
Compression Ratio	≥ 25 (@50PSI)	%	ASTM D695
UL Certification	V-0, 5V	-	UL94
Operating Temperature	-50 ~ 180	$^{\circ}\text{C}$	IEC 600068-2-14

Thermal Characteristics:

Thermal Conductivity	1.5 (± 0.2)	W / m·K	ASTM D5470
Thermal Resistance	≤ 1.5 (@20PSI/1mm)	$^{\circ}\text{Cin}^2/\text{W}$	ASTM D5470

Electrical Properties:

Breakdown Voltage	≥ 8	KV/mm	ASTM D149
Volume Resistivity	$\geq 10^{10}$	$\Omega\cdot\text{cm}$	ASTM D257
Dielectric constant	≥ 2	@1MHz	ASTM D150
Dielectric loss	≤ 0.1	@1MHz	ASTM D150

Global EMI Shielding Technology Center
12420 Race Track Rd., Tampa, Florida 33626
866.TECH.EMI (866.832.4364) † 813.855.6921 ‡ 813.855.3291

www.LeaderTechInc.com



EMI/RFI Board, Enclosure, Cable Shielding & Thermal Solutions



Copyright© Leader Tech, Inc. 2024

STATEMENT IN LIEU OF WARRANTY: All technical information and data in this document is based on tests and is believed to be accurate and reliable. Nevertheless, since the products described herein are not provided to conform with mutually accepted specifications and the use thereof is unknown, the manufacturer and seller of the products do not guarantee results, freedom from patent infringement, or suitability of the products for any application thereof. The manufacturer and seller of the products described in this document will provide all possible technical assistance and will replace any products proven defective. No statement or recommendations made by the manufacturer or seller not contained herein shall have any force of effect unless in conformity with an agreement signed by an officer of the seller and manufacturer. Product testing by the purchaser is recommended in order to confirm expected results. copyright© Leader Tech, Inc. 2024